Canon

Color imageRUNNER® LBP5975
LBP5970

Color imageRUNNER® LBP5460

imageRUNNER® LBP3460

desktop productivity

color and/or black and white

networked

OFFICE SOLUTIONS

Color imageRUNNER® LBP5975 LBP5970

PRODUCT SPECIFICATIONS

Main Unit

GENERAL	Type:	Desktop Color Laser Printer
	Printing Method:	Electrophoto Method (Color RAPID Fusing System)
	Developing System:	Dry Dual Component Developing System
	Standard PDL:	UFR II/PCL 5c/6
	Optional PDL Support:	PostScript® 3™ Emulation (PS ROM 98B/98C)
	Power Supply:	120V-127V 60Hz
	Plug:	NEMA 5-15P
HARDWARE	Memory (RAM):	Standard 256MB, Maximum 768MB*
	Hard Disk Drive:	Optional 30GB
	CPU:	R4000 Series (400 MHz),** MIPS64 Series (533 MHz)**
INTERFACE	Connections:	10/100Base-TX (RJ-45), Wireless LAN (IEEE 802.11)***
	Other Interface:	USB 2.0 Hi-Speed/USB Full-Speed (USB 1.1 Equivalent)
	User Interface:	LCD 16 Characters x 1 Line, 11 LED Indicators, 9 Operation Keys
SPEED	Print Speed (B/W, Color):	31/30 ppm (Letter)
	Warm-Up Time:	0 Seconds from Standby 30 Seconds or Less from Power On
	First-Print Time:	LBP5975: 8.9 Seconds (B/W); 10.4 Seconds (Full Color) LBP5970: 7.5 Seconds (B/W); 9.0 Seconds (Full Color)
RESOLUTION	Print:	UFR II: 1200 x 1200 dpi▲ (Super Fine Mode) 2400-dpi equivalent x 600 dpi (Fine Mode) PCL5c/6: 2400-dpi equivalent x 600 dpi PS3 (Optional): 1200 x 1200 dpi▲ (Text and Line Only) 2400-dpi equivalent x 600 dpi
	Engine:	1200 x 1200 dpi
	Halftone:	256 Gradations (Continuous-Tone)
PRINT DRIVERS	UFR II:	Windows® 2000/XP/Windows Vista®/Server 2003/ Server 2008 Citrix MetaFrame Macintosh® (OS 10.3.3 or Later) Novell® NetWare® v3.20/4.1/4.11/4.20/5.0/5.1/6.0/6.5 (IPX/SPX)
	PCL 5c/6:	Windows 2000/XP/Windows Vista/Server 2003/ Server 2008 Citrix MetaFrame
	PS3 Emulation:	Windows 2000/XP/Windows Vista/Server 2003/ Server 2008 Citrix MetaFrame Macintosh (OS 10.3.3 or Later)
SIZE	Dimensions (H x W x D):	LBP5975: 17-1/4" x 21" x 25" (Main Unit) LBP5970: 15" x 21" x 25" (Main Unit)
	Installation Space (W x D):	21-1/2" x 37-3/5" (When Multi-Purpose Tray is Extended)
	Weight:	LBP5975: Approx. 115.7 lb. (52.5kg)† LBP5970: Approx. 106.9 lb. (48.5kg)†
POWER CONSUMPTION (Average)	Operating:	653W (Approx., Average)
	Standby:	34W (Approx., Average)
	Power Save Mode:	14W (Approx., Average)
	Deep Sleep Mode:	1W (Approx., Average)

PAPER SOURCES	Standard Cassette:	230-Sheet Paper Cassette (20 lb. Bond) 90-Sheet Multi-Purpose Tray
	Optional:	550-Sheet Paper Cassette (Up to 3)
	Maximum:	1,970 Sheets
PAPER SIZES	Cassettes:	Ledger, Legal, Letter, Executive
	Multi-Purpose Tray:	Ledger, Legal, Statement, Letter, Executive, Custom Sizes (Width: 3-7/8" to 5-3/4"; Length: 5-1/2" to 18"), Long Size Paper (Width: 8-3/8" to 11-3/4"; Length: 18" to 47-1/4"), and Envelopes
	Maximum Size:	11" x 17" (305mm x 457mm)
PAPER WEIGHT	Cassettes:	17 lb. Bond to 28 lb. Bond
	Multi-Purpose Tray:	17 lb. Bond to 80 lb. Cover
PAPER HANDLING	Paper Output:	Face-Down
	Output Capacity:	Approx. 250 Sheets (20 lb. Bond)
	Duplexing:	Standard Automatic Trayless Duplexing (Executive to 11" x 17")
FINISHING (LBP5975 Only)	**Corner Stapling**	
	Staple Positions:	Letter: Portrait–Upper Left, Lower Right Landscape–Upper Right, Lower Left Executive: Portrait–Upper Left, Lower Right Landscape–Upper Right, Lower Left Ledger: Portrait–Upper Right, Lower Left Landscape–Upper Left, Lower Right
	Output Capacity:	Up to 15 Pages Per Set (Letter/Executive/Ledger)
	Paper Weight:	17 lb. Bond to 28 lb. Bond
TONER (Estimated Yield)	Black:	10,000 images at 5% coverage††
	Full Color:	6,000 images at 5% coverage††

Optional Accessories

PAPER FEEDER UNIT PF-98B†††	Paper Sizes:	Standard: Ledger, Legal, Letter, Executive Custom: Width 8-3/8" to 11-3/4"; Length 8-3/8" to 17"
	Cassette Capacity:	550 Sheets x 3 Cassettes (20 lb. Bond)
	Dimensions (H x W x D):	5-5/8" x 21-1/2" x 27-1/2"
	Weight:	Approx. 24.3 lb. (11kg)
OTHER	PostScript 3 Emulation/Barcode Printing ROM A-98B•	
	PostScript 3 Emulation ROM A-98C•	
	Wireless Network Interface Board NB-W2	
	Hard Disk Kit HD-98B	
	Cabinet W1 (Small),■ X1 (Large)■■	
	Expansion RAM ER-128A, ER-256A, ER-512A*	

* One memory slot available for expanding memory.
** The upper limit of the frequency range.
*** Through optional Wireless LAN Kit.
▲ If 1200-dpi print is selected, engine speed will be reduced.
† Excluding the toner cartridges and drum cartridges.
†† When printing letter-sized paper at 5% page coverage with the default print density settings.
††† Up to three additional paper cassettes can be added.
• PostScript 3 Emulation/Barcode Printing ROM A-98B and PostScript 3 Emulation ROM A-98C cannot be installed together.
■ Up to three additional paper cassettes can be installed when Cabinet-W1 is attached.
■■ Up to one additional paper cassette can be installed when Cabinet-X1 is attached.

Color imageRUNNER® LBP5460

PRODUCT SPECIFICATIONS

Main Unit

GENERAL	Type:	Desktop Color Laser Printer
	Printing Method:	Electrophoto Method (Color RAPID Fusing System)
	Developing System:	Dry Dual Component Developing System
	Standard PDL:	UFR II/PCL 5c/PCL6/PostScript 3 Emulation
	Power Supply:	120V 60Hz
	Plug:	NEMA 5-15P
HARDWARE	Memory (RAM):	Standard 256 MB, Maximum 768 MB*
	Hard Disk Drive:	Optional 60GB
	CPU:	R4000 Series (400 MHz)** MIPS64 Series (533 MHz)**
INTERFACE	Connections:	10/100Base-TX (RJ-45) Wireless LAN (IEEE 802.11)***
	Other Interface:	USB 2.0 Hi-Speed USB Full-Speed (USB 1.1 Equivalent)
	User Interface:	LCD 22 Characters x 5 Lines, 9 LED Indicators, 10 Operation Keys
SPEED	Print Speed (B/W, Color):	Up to 31/31 ppm (Letter)
	Warm-Up Time:	7 Seconds from Standby 60 Seconds or Less from Power On
	First-Print Time:	10.2 Seconds (B/W) 10.4 Seconds (Color)
RESOLUTION	Print:	2400-dpi equivalent x 600 dpi
	Engine:	600 x 600 dpi
	Halftone:	256 Gradations (Continuous-Tone)
PRINT DRIVERS	UFR II/PS3:	Windows 2000/XP/Windows Vista/Server 2003/Server 2008 Citrix MetaFrame Macintosh (OS 10.4 or Later) Novell NetWare v3.20/4.1/4.11/4.20/5.0/5.1/5.5 (IPX/SPX) Novell NetWare v6.0/6.5 (TCP/IP)
	PCL 5c/6:	Windows 2000/XP/Windows Vista/Server 2003/Server 2008 Citrix MetaFrame Novell NetWare v3.20/4.1/4.11/4.20/5.0/5.1/5.5 (IPX/SPX) Novell NetWare v6.0/6.5 (TCP/IP)
SIZE	Dimensions (H x W x D):	14-5/8" x 20-1/4" x 20-3/4" (Main Unit)
	Installation Space (W x D):	29-1/8" x 32-1/4" (When Multi-Purpose Tray is Extended)
	Weight:	Approx. 68.3 lb. (31.0 kg)†
POWER CONSUMPTION (Average)	Operating:	573W (Approx., Average)
	Standby:	47W (Approx., Average)
	Power Save Mode:	18W (Approx., Average)
	Deep Sleep Mode:	1.8W (Approx., Average)

PAPER SOURCES	Standard:	250-Sheet Paper Cassette (20 lb. Bond) 100-Sheet Multi-Purpose Tray
	Optional:	500-Sheet Paper Cassette
	Maximum:	850 Sheets
PAPER SIZES	Standard Cassette:	Letter, Executive, Custom Sizes (Width: 5-7/8" to 8-1/2"; Length: 8-1/4" to 11-5/8")
	Multi-Purpose Tray:	Legal, Letter, Executive, Statement, Custom Sizes (Width: 3-7/8" to 8-1/2"; Length: 5-3/4" to 14"), and Envelopes
	Optional Cassette:	Legal, Letter, Executive, Custom Sizes (Width: 5-7/8" to 8-1/2"; Length: 8-1/4" to 14")
	Maximum Size:	Legal (216mm × 355.6mm)
PAPER WEIGHT	Standard Cassette:	16 lb. Bond to 60 lb. Cover
	Multi-Purpose Tray:	16 lb. Bond to 80 lb. Cover
	Optional Cassette:	16 lb. Bond to 65 lb. Cover
PAPER HANDLING	Paper Output:	Face-Down
	Output Capacity:	Approx. 250 Sheets (20 lb. Bond)
	Duplexing:	Standard Automatic Trayless Duplexing (Executive to Legal)
TONER †† ▲ (Estimated Yield)	Average Black (GPR-29):	10,000 Standard Pages
	Average Composite Cyan/Magenta/Yellow (GPR-29):	8,500 Standard Pages

Optional Accessories

PAPER FEEDER UNIT PF-723‡	Paper Sizes:	Legal, Letter, Executive, Custom Sizes (Width: 5-7/8" to 8-1/2"; Length: 8-1/4" to 14")
	Paper Capacity:	500 Sheets (20 lb. Bond)
	Dimensions (H x W x D):	6-3/8" x 20-1/4" x 20-3/4"
	Weight:	Approx. 17.2 lb. (7.8 kg)
OTHER	Barcode Printing ROM A-723A	
	Wireless Network Interface Board NB-W2	
	Hard Disk Kit HD-723	
	Expansion RAM ER-128A, ER-256A, ER-512A*	

* One memory slot available for expanding memory.
** The upper limit of the frequency range.
*** Through optional Wireless LAN Kit.
† Excluding the toner cartridges.
†† Toner cartridge yield in accordance with ISO/IEC 19798.
▲ Main unit ships with starter cartridges: Average Black (GPR-29) Starter Cartridge: 3,000 standard pages; Average Composite Cyan/Magenta/Yellow (GPR-29) Starter Cartridge: 4,100 standard pages.
‡ Up to one paper cassette can be added.

imageRUNNER® LBP3460

PRODUCT SPECIFICATIONS

Main Unit

GENERAL	Type:	Desktop Laser Printer
	Printing Method:	Electrophoto Method (RAPID Fusing System)
	Developing System:	Dry Dual Component Developing System
	Standard PDL:	UFR II/PCL 5e/6
	Power Supply:	100-127V, 50/60Hz
	Plug:	NEMA 5-15P
HARDWARE	Memory:	Standard 64MB RAM, Maximum 320MB RAM*
	CPU:	R4000-333MHz**
NETWORK	Connections:	10/100Base-TX (RJ-45)
	Other Interface:	USB 2.0 Hi-Speed USB Full-Speed (USB 1.1 Equivalent)
	User Interface:	LCD 16 Characters x 1 Line, 8 LED Indicators, 8 Operation Keys
SPEED	Print Speed (B/W):	35 ppm (Letter)
	Warm-Up Time:	0 Seconds From Standby 9 Seconds After Powering On
	First-Print Time:	8.0 Seconds
RESOLUTION	Print:	UFR II/PCL 5e/6: 600 x 600 dpi 2400-dpi equivalent x 600 dpi
	Engine:	600 x 600 dpi
	Halftone:	256 Gradations (Continuous-Tone)
PRINT DRIVERS	UFR II:	Windows 2000/XP/Windows Vista/Server 2003/ Server 2008 Citrix MetaFrame Macintosh (OS 10.2.8 or Later)
	PCL 5c/6:	Windows 2000/XP/Windows Vista/Server 2003/ Server 2008 CitrixMetaFrame
SIZE	Dimensions (H x W x D):	10-3/4" x 17-5/8" x 16-1/4" (Main Unit)
	Installation Space (W x D):	17-5/8" x 24-1/2" (When Multi-Purpose Tray is Extended)
	Weight:	Approx. 35.5 lb. (16.1kg)***
POWER CONSUMPTION (Average)	Operating:	580W (Approx., Average)
	Standby:	10W (Approx., Average)
	Deep Sleep Mode:	7W (Approx., Average)

PAPER SOURCES	Standard:	250-Sheet Paper Cassette (20 lb. Bond) 100-Sheet Multi-Purpose Tray
	Optional:	500-Sheet Paper Cassette
	Maximum:	850 Sheets
PAPER SIZES	Drawers:	Legal, Letter, Executive, Custom Sizes (Width: 5-7/8" to 8-1/2"; Length: 8-3/8" x 14")
	Multi-Purpose Tray:	Legal, Letter, Executive,Statement, Index Card, Custom Sizes (Width: 3"to 8-1/2"; Length: 5" to 14") and Envelopes
	Maximum Size:	Legal (216mm x 355.6mm)
PAPER WEIGHT	Cassettes:	17 lb. Bond to 35 lb. Bond
	Multi-Purpose Tray:	17 lb. Bond to 65 lb. Cover
PAPER HANDLING	Paper Output:	Face-Down/Face-Up
	Output Capacity:	Approx. 250 Sheets (Face-Down) Approx. 50 Sheets (Face-Up)
	Duplexing:	Standard Automatic Trayless Duplexing (Legal, Letter)
TONER (Estimated Yield)	Black (Cartridge 110):	6,000 Standard Pages†
	Black (Cartridge 110 II):	12,000 Standard Pages†

Optional Accessories

PAPER FEEDER UNIT PF-36††	Paper Sizes:	Legal, Letter, Executive, Custom Sizes (Width: 5-7/8" to 8-1/2"; Length: 8-3/8" x 14")
	Cassette Capacity:	500 Sheets (20 lb. Bond)
	Dimensions (H x W x D):	6-5/8" x 17-5/8" x 18-7/8"
	Weight:	Approx. 12.4 lb. (5.6kg)
OTHER	Expansion RAM ER-128A, ER-256A, ER-512A*	

* One memory slot available for expanding memory.
** The upper limit of the frequency range.
*** Excluding the toner cartridges and drum cartridges.
† Toner cartridge yield in accordance with ISO/IEC 19752.
†† One additional paper cassette can be added.

Canon
imageANYWARE

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Plaza
Lake Success, NY 11042

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has determined that these products meet the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. CANON, IMAGERUNNER, and the GENUINE logo are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. IMAGEWARE is a registered trademark of Canon U.S.A., Inc. in the United States and is a trademark of Canon Inc. in certain other countries. IMAGEANYWARE is a trademark of Canon. All other referenced product names and marks are trademarks of their respective owners and hereby acknowledged.
Specifications and availability subject to change without notice. All printer output images are simulated.
©2009 Canon U.S.A., Inc. All rights reserved.

0133W076
0709-LBPSERIES-6M-LMC